


Performance curves



The performance curves are based on air at a temperature of 15 °C and an atmospheric pressure of 1013 mbar with a tolerance of $\pm 10\%$. The total pressure differences are valid for suction and ambient temperature up to 25 °C. For other conditions please get in touch with us.

Every 4RB pump can be used both as vacuum pump and compressor in continuous operation over the total performance curve range. The motors are available as standard in protection category IP 55 and insulation class F.

Selection and ordering data										
Type 4RB 420										
No.	Fre- quency	Rated			Max. differential pressure ²⁾		Sound pressure level ³⁾	Efficiency ⁴⁾	Weight Approx.	Order No.
		Voltage ¹⁾	Current	Power	Vacuum	Pressure				
	Hz	V	A	kW	mbar		dB(A)	0	kg	
IE3 3~ 50/60 Hz, IP55, Insulation material class F(UL certificate number E481218)										
1	50	190-210△	6.9 △	1,75	-500	460	64	IE3	38	4RB 420-0AP21-1
	60	190-210 YY/ 380-420 Y	7,8 YY / 3.9Y	2,0	-500	410	67	IE3		
2	50	190-210△	9.9 △	2,5	-500	730	64	IE3	43	4RB 420-0AP31-1
	60	220-240 YY / 380-420 Y	12.0 YY/ 6.0 Y	3,0	-550	700	67	IE3		
3	50	190-210△	13.3 △	3,45	-500	830	67	IE3	47	4RB 420-0AP41-1
	60	220-240 YY / 380-420 Y	15.2 YY/ 7.6 Y	4,0	-560	950	73	IE3		
IE3 3~ 50/60 Hz, IP55, Insulation material class F(UL certificate number E481218)										
1	50	220-240 △ / 380-420 Y	6,0 △/ 3.5Y	1,75	-500	460	64	IE3	38	4RB 420-0AP26-1
	60	220-240 YY / 440-480 Y	6,8 △/ 3.4 Y	2,0	-500	410	67	IE3		
2	50	220-240 △ / 380-420 Y	8.6 △/ 5.0Y	2,5	-500	730	64	IE3	43	4RB 420-0AP36-1
	60	220-240 YY / 440-480 Y	10,4 △/ 5.2 Y	3,0	-550	700	67	IE3		
3	50	220-240 △ / 380-420 Y	11.6 △/ 6.7Y	3,45	-500	830	67	IE3	47	4RB 420-0AP46-1
	60	220-240 YY / 440-480 Y	13,2 △/ 6.6 Y	4,0	-560	950	73	IE3		
IE3 3~ 50/60 Hz, IP55, Insulation material class F(UL certificate number E481218)										
1	50	220-240 △ / 380-420 Y	6,0 △/ 3,5Y	1,75	-500	460	64	IE3	38	4RB 420-0AQ26-1
	60	440-480 Y	3,4 Y	2,0	-500	410	67	IE3		
2	50	220-240 △ / 380-420 Y	8.6△/ 5,0Y	2,5	-500	730	64	IE3	43	4RB 420-0AQ36-1
	60	440-480 Y	5,2 Y	3,0	-550	700	67	IE3		
3	50	220-240 △ / 380-420 Y	11,6 △/ 6,7Y	3,45	-500	830	67	IE3	47	4RB 420-0AQ46-1
	60	440-480 Y	6,6 Y	4,0	-560	950	73	IE3		

- 1) In case of frequency converter operation the standard motor insulation system is suitable for converter input voltages up to 500 V.
- 2) Relief valves available for limiting differential pressure.
- 3) Measuring surface sound pressure level acc. to EN ISO 3744, measured with an equivalent unit at a distance of 1 m. The pump is throttled to an average suction pressure, with piping connected, but no relief valves fitted, tolerance ±3 dB (A).
- 4) The motors according to NEMA MG1-12. NP=NEMA Premium; NEMA Premium includes IE3.

All 4RB blowers match the 2006/42/EC (machinery) and 2014/35/EU (low voltage) directives and the EN 60034 norm "Rotating electrical machines".

Service factor (SF) and motor efficiency according NEMA MG1-12.

Voltage tolerances for three phase motors are +/-10%.

The frequency tolerance is +/- 2 % maximum.

Motor for alternate voltages						
Voltage range			Efficiency			
50 Hz	60Hz	60 Hz		4RB ...-0. □ . □ -1		
3~						
200 VΔ	200 V YY / 230 VΔ / 400 VY		•		P	1
190-210 VΔ	190-210 VYY / 220-240 VΔ / 380-420VY	IE3				
200 V YY / 230 VΔ / 400 VY	230 V YY / 460 VY		•		P	6
190-210 VYY / 220-240 VΔ / 380-420VY	220-240 VYY / 440-480VY	IE3				
475-525 V Y	550-600 V Y		•		Q	3
475-525 VΔ	550-600 VΔ					
220-240 VΔ / 380-420VY	440-480VY	IE3	•		Q	6
400 VΔ / 690 V Y	460 VΔ					

Changes in particular of the quoted performance curve, data and weights may occur without prior notice. The data given do not constitute an obligation from our side to deliver as shown.